

## iCombi Classic overview of models.

Classic features, multiple possibilities.

The iCombi Classic is available in many different sizes, as ultimately its performance fits your needs and not the other way around. 20 meals or 2,000? Front of house cooking? Size of kitchen? Electricity? Gas? 6-1/1? 20-2/1? Which model belongs in your kitchen?

All the options, equipment features and accessories at: [rational-online.com](http://rational-online.com)



iCombi Classic	6-1/1	10-1/1	6-2/1	10-2/1	20-1/1	20-2/1
<b>Electric and gas</b>						
Capacity	6 × 1/1 GN	10 × 1/1 GN	6 × 2/1 GN	10 × 2/1 GN	20 × 1/1 GN	20 × 2/1 GN
Number of meals per day	30–100	80–150	60–160	150–300	150–300	300–500
Lengthwise loading (GN)	1/1, 1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1, 2/4 GN	2/1, 1/1, 2/4 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1, 2/4 GN
Width	850 mm	850 mm	1072 mm	1072 mm	877 mm	1082 mm
Depth (incl. door handle)	842 mm	842 mm	1042 mm	1042 mm	913 mm	1117 mm
Height	754 mm	1014 mm	754 mm	1014 mm	1807 mm	1807 mm
Water inlet	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"
Water outlet	DN 50	DN 50	DN 50	DN 50	DN 50	DN 50
Water pressure	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar
<b>Electric</b>						
Weight	93 kg	121 kg	131 kg	160 kg	231 kg	304 kg
Connected load	10.8 kW	18.9 kW	22.4 kW	37.4 kW	37.2 kW	67.9 kW
Fuse	3 × 16 A	3 × 32 A	3 × 35 A	3 × 63 A	3 × 63 A	3 × 100 A
Mains connection	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V
Connected load convection mode	10.25 kW	18 kW	21.6 kW	36 kW	36 kW	66 kW
Connected load steam mode	9 kW	18 kW	18 kW	36 kW	36 kW	54 kW
<b>Gas</b>						
Weight	101 kg	139 kg	128 kg	184 kg	276 kg	371 kg
Electrical rating	0.6 kW	0.9 kW	0.9 kW	1.5 kW	1.3 kW	2.2 kW
Fuse	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A
Mains connection	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V
Gas supply/connection	3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG
<b>Natural gas /LPG G31/LPG G30*</b>						
Max. Nominal thermal load	13 kW/13 kW/ 13.5 kW	22 kW/22 kW/ 23 kW	28 kW/28 kW/ 29.5 kW	40 kW/40 kW/ 42 kW	42 kW/42 kW/ 44 kW	80 kW/80 kW/ 84 kW
Convection mode output	13 kW/13 kW/ 13.5 kW	22 kW/22 kW/ 23 kW	28 kW/28 kW/ 29.5 kW	40 kW/40 kW/ 42 kW	42 kW/42 kW/ 44 kW	80 kW/80 kW/ 84 kW
Steam mode output	12 kW/12 kW/ 12.5 kW	20 kW/20 kW/ 21 kW	21 kW/21 kW/ 22 kW	40 kW/40 kW/ 42 kW	38 kW/38 kW/ 40 kW	51 kW/51 kW/ 53.5 kW

\* To guarantee proper operation, the appropriate connection flow pressure must be ensured:  
 Natural gas H G20: 18–25 mbar (0.261–0.363 psi), Natural gas L G25: 20–30 mbar (0.290–0.435 psi), LPG G30 and G31: 25–57.5 mbar (0.363–0.834 psi).  
 XS and 20-2/1 Electric: ENERGY STAR excludes these unit sizes from certification.

