

iCombi Classic overview of models.

Classic features, multiple possibilities.



The iCombi Classic is available in many different sizes, as ultimately its performance fits your needs and not the other way around. 20 meals or 2,000? Front of house cooking? Size of kitchen? Electricity? Gas? 6-1/1? 20-2/1? Which model belongs in your kitchen?

All the options, equipment features and accessories at: rational-online.com

| iCombi Classic | 6-1/1 | 10-1/1 | 6-2/1 | 10-2/1 | 20-1/1 | 20-2/1 |
|--------------------------------------|----------------------------|----------------------------|-------------------------|-----------------------|----------------------------|-------------------------|
| Electric and gas | | | | | | |
| Capacity | 6 × 1/1 GN | 10 × 1/1 GN | 6 × 2/1 GN | 10 × 2/1 GN | 20 × 1/1 GN | 20 × 2/1 GN |
| Number of meals per day | 30–100 | 80–150 | 60–160 | 150–300 | 150–300 | 300–500 |
| Lengthwise loading (GN) | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 2/1, 1/1, 2/4 GN | 2/1, 1/1, 2/4 GN | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 2/1, 1/1, 2/4 GN |
| Width | 850 mm | 850 mm | 1072 mm | 1072 mm | 877 mm | 1082 mm |
| Depth (incl. door handle) | 842 mm | 842 mm | 1042 mm | 1042 mm | 913 mm | 1117 mm |
| Height | 754 mm | 1014 mm | 754 mm | 1014 mm | 1807 mm | 1807 mm |
| Water inlet | R 3/4" | R 3/4" | R 3/4" | R 3/4" | R 3/4" | R 3/4" |
| Water outlet | DN 50 | DN 50 | DN 50 | DN 50 | DN 50 | DN 50 |
| Water pressure | 1.0 - 6.0 bar | 1.0 - 6.0 bar | 1.0 - 6.0 bar | 1.0 - 6.0 bar | 1.0 - 6.0 bar | 1.0 - 6.0 bar |
| Electric | | | | | | |
| Weight | 93 kg | 121 kg | 131 kg | 160 kg | 231 kg | 304 kg |
| Connected load | 10.8 kW | 18.9 kW | 22.4 kW | 37.4 kW | 37.2 kW | 67.9 kW |
| Fuse | 3 × 16 A | 3 × 32 A | 3 × 35 A | 3 × 63 A | 3 × 63 A | 3 × 100 A |
| Mains connection | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V |
| Connected load convection mode | 10.25 kW | 18 kW | 21.6 kW | 36 kW | 36 kW | 66 kW |
| Connected load steam mode | 9 kW | 18 kW | 18 kW | 36 kW | 36 kW | 54 kW |
| Gas | | | | | | |
| Weight | 101 kg | 139 kg | 128 kg | 184 kg | 276 kg | 371 kg |
| Electrical rating | 0.6 kW | 0.9 kW | 0.9 kW | 1.5 kW | 1.3 kW | 2.2 kW |
| Fuse | 1 × 16 A | 1 × 16 A | 1 × 16 A | 1 × 16 A | 1 × 16 A | 1 × 16 A |
| Mains connection | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V |
| Gas supply/connection | 3/4" IG | 3/4" IG | 3/4" IG | 3/4" IG | 3/4" IG | 3/4" IG |
| Natural gas /LPG G31/LPG G30* | | | | | | |
| Max. Nominal thermal load | 13 kW/13 kW/ 13.5 kW | 22 kW/22 kW/ 23 kW | 28 kW/28 kW/ 29.5 kW | 40 kW/40 kW/ 42 kW | 42 kW/42 kW/ 44 kW | 80 kW/80 kW/ 84 kW |
| Convection mode output | 13 kW/13 kW/ 13.5 kW | 22 kW/22 kW/ 23 kW | 28 kW/28 kW/ 29.5 kW | 40 kW/40 kW/ 42 kW | 42 kW/42 kW/ 44 kW | 80 kW/80 kW/ 84 kW |
| Steam mode output | 12 kW/12 kW/ 12.5 kW | 20 kW/20 kW/ 21 kW | 21 kW/21 kW/ 22 kW | 40 kW/40 kW/ 42 kW | 38 kW/38 kW/ 40 kW | 51 kW/51 kW/ 53.5 kW |

* To guarantee proper operation, the appropriate connection flow pressure must be ensured:
 Natural gas H G20: 18–25 mbar (0.261–0.363 psi), Natural gas L G25: 20–30 mbar (0.290–0.435 psi), LPG G30 and G31: 25–57.5 mbar (0.363–0.834 psi).
 XS and 20-2/1 Electric: ENERGY STAR excludes these unit sizes from certification.

